



# QPC-6CooD-V3895

600TVL, OSD, 4~9mm, 3-Axis Dome Camera

- 600TVL
- 3.8~9.5mm VF Lens
- OSD,AWB,SLBC
- 3-Axis Dome



## Features :

- 1/3" Sony Super HAD II CCD
- 600TVL Ultra High Resolution
- Built-in 3.8~9.5mm DC Iris Vary focal Lens
- OSD, AGC, SBLC, AWB, Privacy Mask,
- Flickerless, Mirror Fn, Motion Detection
- 2<sup>nd</sup> Video O/p for On-site Configuration
- 3 Axis Gimbal (Indoor Dome)

## Specification :

Model	QPC-6CooD-V3895
Image Sensor	1/3 Inch Sony Super HAD II CCD
Total / Effective Pixels	752(H) x 582(V) 440K
Horizontal Resolution	600 TV Lines (BW 650TV Lines)
Lens	DC Iris Vari-focal Lens (3.8~9.5mm)
Signal System	PAL
Scanning System	2:1 Interlace
Scanning Frequency (H)/ (V)	15.625 KHz / 50 Hz
Video Output	1.0V p-p (75Ω Composite)
S/N Ratio	More than 50dB(AGC Off)
Min.illumination	0.05Lux (Color)
OSD	English, Chinese
Digital Noise Reduction	Low, Middle, High, Off
White Balance	Auto
AGC	On/Off
SBLC	Off, Low, Middle,High
Flickerless	On/Off
Privacy Zone	On/Off (4 Programmable Zone)
Motion Function	On/Off (4 Programmable Zone)
Mirror Function	Horizontal
Shutter Speed	1/50-1/120,000Sec.
Manual Shutter Speed	1/50 ~ 1/120K Sec
Supplied Voltage	DC 12V
Power Consumption	Max. 2.2W / 180mA
Dimensions (OxH)	123 x 95 mm
Weight	Approx. 360g